



## Classic exterior & interior emulsion

It is a water based finished for all your humid climate conditions.

### USES

**Sustainable** - When used with Damp Sheath, Classic Exterior Emulsion offers a 3-year waterproofing and performance warranty. For further information, consult the Classics Exterior & interior Emulsion warranty handbook.

**More Efficiency** - Compared to other Emulsion, classics provides great resistance to chalking, cracking, and weathering. Paint adheres to your wall for a longer period of time thanks to the modified acrylic binder than other Emulsion.

**Cost effective** - Classics is more cost-effective in the long run than cement paint because it lasts longer. Moreover, since there is no need for curing, it saves time, labour, and cost during application.

**Bright Shades** - The colours offered by Classics are sleek and tidy, and they last longer than the colours of cement paint. Strong, dark hues are available that offer great concealing.

**Fungal protection** - it provides protection against fungal growth which is better than cement.

## PRODUCT CHARACTERISTICS

### Durability Exterior



**3**  
Yrs

### Shades Available



White & All Shades as per your Requirement

### Application



70 sq ft/ltr/coat

### Availability



### Dilution



### Suitable For Exterior / Interior

### Finish

↓  
Matt Finish   Soft Sheen   Rich Sheen   High Gloss

**MATT FINISH**

Refer to sheen levels in technical details

### Shelf Life



**1**  
Yr

### Re-Coating



**6**  
Hours

## EXTRA INFORMATION

### AFTER APPLICATION CARE

- ▶ Clean all unwanted growth for best performance of paint

### TECHNICAL DETAILS

- A. Drying time:** Surface dry time 30 minutes
- B. Sheen levels:** 8 - 14 at 60°GH
- C. Flash point IS101/1987 Part 1, Sec 6:** NA
- D. Stability of thinned paint:** To be used within 24 hours

### CAUTION TO TAKE

- ▶ Keep out of children's reach and away from food.
- ▶ Should not be swallowed. If you've eaten something, get help right away.
- ▶ Before applying, protect your eyes. In the event of contact with the eyes, flush with water right away and seek simple assistance.
- ▶ Thoroughly wash the skin with soap and water if in contact with product. If irritation occurs or continues, seek medical assistance.
- ▶ Do not inhale spray or vapour. To prevent dust inhalation while sanding and surface preparation, it is advised to wear a suitable nose pad.
- ▶ Never spill leftover paint into waterways or drains. . In the event of spills, contain spillage using sand or soil.
- ▶ No additional Lead, Mercury, or Chromium compounds

### PREVENTIVE MEASURES

- ▶ If the temperature is expected to fall within four hours of application or if the ambient temperature is less than 10°C, avoid applying.
- ▶ Avoid overstretching or overthinning the brush.