



Delux Synthetic Enamel

Surfaces painted with this finish have a bright new appearance thanks to gloss enamel. It creates a hard, stain-resistant layer that is developed. As a result, it acts as a shield for the paint film.

Gives a look which makes others glare.

USES

- **Glossy Apperance :**
Your doors, windows, grills, and gates will have a crystal gloss thanks to Classics Delux Synthetic Enamel.
- **Durable and Robust :**
Classics Delux Synthetic Enamel forms a protective armour around surfaces, is one of the strongest & most resistant paints due to its oil-based lm.

PRODUCT CHARACTERISTICS

Finish

Matt Finish Soft Sheen Rich Sheen **Gloss**

GLOSS

Refer to sheen levels in technical details

Shades Available



White & All Shades as per your Requirement

Application



70 - 80 sq ft/lt/coat

Availability



50 ml — 500 ml — 1 Ltr — 20 Ltr

Shelf Life



1 Yr

Dilution



90 to 100ml for 1 ltr

Use Within 6 Hrs

Usage



Best for **Wood, Wall & all Metal Surfaces**

Re-Coating



6-8 Hours

EXTRA INFORMATION

TECHNICAL DETAILS

A. Drying time: Surface dry time 30 minutes

B. Sheen levels: 8 - 14 at 60°GH

C. Flash point IS101/1987 Part 1, Sec 6: NA

D. Stability of thinned paint: To be used within 24 hours

CAUTION TO TAKE

- ▶ Keep out of children's reach and away from food.
- ▶ Should not be swallowed. If you've eaten something, get help right away.
- ▶ Before applying, protect your eyes. In the event of contact with the eyes, flush with water right away and seek simple assistance.
- ▶ Thoroughly wash the skin with soap and water or continues, seek medical assistance. contact with product. If irritation occurs
- ▶ Do not inhale spray or vapour. To prevent dust inhalation while sanding and surface preparation, it is advised to wear a suitable nose pad.
- ▶ Never spill leftover paint into waterways or drains. In the event of spills, contain spillage using sand or soll.
- ▶ No additional Lead, Mercury, or Chromium compounds

PREVENTIVE MEASURES

- ▶ If the temperature is expected to fail within four hours of application or if the ambient temperature is than 10°C, avoid applying.
- ▶ Avoid ovenstretching or over thinning the brush.
- ▶ Use only Classics Paints machine colourants while tinting.
- ▶ Strain the mixture before using & whisk it well.
- ▶ Before usage and right away after tinter addition, tinted paints require thorough shaking