



## Delux Synthetic White Primer

### USES

It hardens quickly, seals well, and resists fungus, moisture, and wall alkalinity well. It an excellent product for all your base level needs.

## PRODUCT CHARACTERISTICS

### Finish

↓  
Matt Finish   Soft Sheen   Rich Sheen   Gloss

**MATT FINISH**

### Shades Available



White

### Application



80 sq ft/ltr/coat

### Availability



200 ml — 500 ml — 1 Ltr — 4 Ltr — 20 Ltr

### Dilution



**200ml  
for 1 ltr**  
Use Within 6 Hrs

### Shelf Life



**1  
Yrs**

### Time to dry

**6-8 HOURS**

### Usage

Can be used for priming  
plastered walls, asbestos,  
brick work, concrete, Wood  
etc

## EXTRA INFORMATION

### AFTER APPLICATION CARE

- ▶ Clean all unwanted growth for best performance of paint.

### CAUTION TO TAKE

- ▶ Keep out of children's reach and away from food.
- ▶ Should not be swallowed. If you've eaten something, get help right away.
- ▶ Before applying, protect your eyes. In the event of contact with the eyes, flush with water right away and seek simple assistance.
- ▶ Thoroughly wash the skin with. and water if in contact with product. If irritation occurs or continues, seek medical assistance.
- ▶ Do not inhale spray or vapour. To prevent dust inhalation while sanding and surface preparation, it is advised to wear a suitable nose pad.
- ▶ Never spill leftover paint into using sand or soil. sor drains in the event of spills, contain spillage.
- ▶ No additional Lead, Mercury, or Chromium compounds.

### PREVENTIVE MEASURES

- ▶ If the temperature is expected to fall within four hours of application or if the ambient temperature is less than 10°C, avoid applying.
- ▶ Avoid overstretching or over thinning the brush.
- ▶ Strain the mixture before using & whisk it well.