



Industrial Black (Chalu Black Japan / Black Primer)

Our Industrial Black Paint delivers a durable, corrosion-resistant finish for metal, wood, surfaces, and walls. Ideal for both indoor and outdoor use, it ensures superior coverage and quick drying times for a professional look.

USES

Shades - Better and brighter colours are offered by Industrial black.

PRODUCT CHARACTERISTICS

Dilution



**200ml
for 1 Ltr**

Use Within 6 Hrs

Application



60 sq ft/lt/coat

Shelf Life



**1
Year**

Availability



0.5 Ltr — 1 Ltr — 4 Ltr — 17 Ltr

Finish

Matt Low Sheen High Sheen **Semi Gloss**

SEMI GLOSS

Refer to sheen levels in technical details

EXTRA INFORMATION

CAUTION TO TAKE

- ▶ It can catch fire
- ▶ Should not be swallowed. If you've eaten something, get help right away.
- ▶ Before applying, protect your eyes. In the event of contact with the eyes, flush with water right away and seek simple assistance.
- ▶ Thoroughly wash the skin with soap and water if in contact with product. If irritation occurs or continues, seek medical assistance.
- ▶ Do not inhale spray or vapour. To prevent dust inhalation while sanding and surface preparation, it is advised to wear a suitable nose pad.
- ▶ Never spill leftover paint into waterways or drains. In the event of spills, contain spillage using sand or soil.
- ▶ No additional Lead, Mercury, or Chromium compounds.

PREVENTIVE MEASURES

- ▶ If the temperature is expected to fall within four hours of application or if the ambient temperature is less than 10°C, avoid applying.
- ▶ Avoid overstretching or over thinning the brush,
- ▶ Use only Classics Paints colourants while tinting,
- ▶ Strain the mixture before using & whisk it well.
- ▶ Before usage and right away after tinter addition, tinted paints require thorough shaking.

AFTER APPLICATION CARE

- ▶ To remove any stains use a sponge to clean it, soap solution can be used for better results. Make sure you can let the surface dry for 1 weeks before you started