



Regal Red Oxide

The best primer for all your metal surfaces. The regal red oxide makes sure your surface is rust & corrosion free for a long term. Keeps your surface free from unwanted rusting.

USES

Our Regal Red Oxide provides a matt look which makes the surface look richer & brighter. Its' great anti- settling features add to the coverage & smooth flow it offers.

PRODUCT CHARACTERISTICS

Finish



Matt Finish Soft Sheen Rich Sheen Gloss

MATT FINISH

Refer to sheen levels in technical details

Shades Available



Red Oxide

Application



60-80 sq ft/ltr/coat

Availability



200 ml — 500 ml — 1 Ltr — 4 Ltr — 20 Ltr

Dilution



**200ml
for 1 ltr**

Use Within 6 Hrs

Shelf Life



**1
Yr**

Time to dry

8-10 HOURS

Usage



Can be used for Priming
Plastered Walls, Asbestos,
Brick Work, Concrete,
wood & Metal.

Re-Coating



**Second
Day**

EXTRA INFORMATION

TECHNICAL DETAILS

- A. Drying time:** Surface dry time 30 minutes
- B. Sheen levels:** 8 - 14 at 60°GH
- C. Flash point IS101/1987 Part 1, Sec 6: NA**
- D. Stability of thinned paint:** To be used within 24 hours

CAUTION TO TAKE

- ▶ Keep out of children's reach and away from food.
- ▶ Should not be swallowed. If you've eaten something, get help right away.
- ▶ Before applying, protect your eyes. In the event of contact with the eyes, flush with water right away and seek simple assistance.
- ▶ Thoroughly wash the skin with. and water if in contact with product. If irritation occurs or continues, seek medical assistance.
- ▶ Do not inhale spray or vapour. To prevent dust inhalation while sanding and surface preparation, it is advised to wear a suitable nose pad.
- ▶ Never spill leftover paint into using sand or soil. sor drains in the event of spills, contain spillage
- ▶ No additional Lead, Mercury, or Chromium compounds

PREVENTIVE MEASURES

- ▶ If the temperature is expected to fall within four hours of application or if the ambient temperature is less than 10°C, avoid applying.
- ▶ Avoid overstretching or thinning the brush.
- ▶ This product might catch fire
- ▶ Contact with skin & eyes is not advisable
- ▶ Work in a a with good air circulation. Fut on safety gear, such as gloves and overalls.
- ▶ Keep the product at room temperature, in areas with good ventilation, and away from flames and combustion.
- ▶ If settling is observable, mis the substance until it is homogeneous before using