



Xtra Power Play Floor Paint

A water-based bridging all acrylic emulsion provides concrete and cement-based floors with outstanding productivity and aesthetic appeal.

USES

Shine : The concrete floors look beautiful because of good shine.

Sustainable : It offers great adherence to a substrate made of concrete.

High Abrasion Tolerance : Film with better abrasion resistance will last longer.

Warranty : Our product provides a thorough Three-year performance warranty for film integrity on concrete pavement blocks.

PRODUCT CHARACTERISTICS

Weather Support



Top Class

Shades Available



White

& all shades as per your requirement

Application



30 sq ft/ltr/coat
(For Best Performance Apply 3 Coats)

Availability



Re-Coating



4 Hours

Dilution



10% Water

Use Within 6 Hrs

Washability



Very High

Advanced Services

Shade as per your Requirements.
T&C*

Shelf Life



2 Yrs

**Suitable For
Exterior & Interior**

Durability Exterior



3 Yrs

EXTRA INFORMATION

AFTER APPLICATION CARE

- ▶ Foot traffic must wait at least 24 hours before it can begin, and regular traffic must wait 72 hours before it can begin. Maintain regular washing and cleaning of the painted surface for optimal performance. Use a wire brush to clean the surface instead.

PREVENTIVE MEASURES

- ▶ During surface preparation, any previous growth of fungus, algae, or moss must be thoroughly removed by vigorous wire brushing.
- ▶ After cleaning, apply Classics Bioblock to the area affected by fungus or algae.
- ▶ Do not apply the paint in frost, dew, rain, fog, or other adverse weather (surface temperatures below 10 °C or above 45 °C).
- ▶ Paints shouldn't be applied directly to a flaky, powdery substrate.
- ▶ Try not to apply on Bituminous/Black-top substrate.
- ▶ After 48 hours of drying at 25°C, allow foot traffic and regular traffic. In conditions that are cold, damp, or humid, drying times must be extended.

CAUTION TO TAKE

- ▶ Could cause harm if swallowed. If there should arise an occurrence of ingestion look for guaranteed clinical consideration.
- ▶ During application, wear eye protection. In the event of eye contact, rinse thoroughly right away and seek medical attention.
- ▶ As a standard practice if there should be an occurrence of skin contact quickly wash skin with cleanser and a lot of water. If irritation develops or persists, see a doctor.
- ▶ Do not inhale vapor or spray, as you would with any other paint. To avoid inhaling dust while sanding or preparing a surface, it is recommended to wear a suitable nose pad. It is also common practice not to pour leftover paint down the drain or into watercourses.
- ▶ Sand or earth can be used to contain spills in the event of one.
- ▶ There are no additional compounds of chromium, arsenic, lead, or mercury.